Gate Valves and Pendulum Valves Specification List

・ UHV and HV Valves Specification List

・ Valve Port Size

・ Please specify Pendulum Valve Type

・ Heat application is available with different specifications

・ Valve adjustment, operation time, and etc. differ depending on Valve installation orientation

・ Gate Valves and Pendulum Valves Specification List

Item	Sub	Specification
・Port Size		☐ 160A ☐ 200A ☐ 250A ☐ 320A ☐ 350A ☐ 400A ☐ 500A ☐ ( )
・Connection Specification		☐ JIS ☐ ISO ☐ その他( )
・Valve Type		☐ IPV ☐ 3PV ☐ APC
・Operation Pressure Request (for IPV and 3PV)		☐ None（0.5MPa Standard ☐ Specified *Please list if specified (MPa)
・Electrical Voltage Request (for APC)		☐ None（DC24V Standar ☐ Specified *Please list if specified ( )
・Sealing Performance		☐ Counter Pressure（VAC-ATM）（Standard) ☐ Other ( )
・Helium Leak Rate	Body	☐ 4.0×10-^11[Pa・m^3/s]（FKM, Standard) ☐ Other ( )
	Gate	☐ 9.0×10-^9[Pa・m^3/s]（FKM, Standard) ☐ Other ( )
・Operating Temperat	Gate	☐ 90℃（Standard) ☐ 120℃ ☐ 150℃ ☐ その他( )
	Actuator	☐ 60℃（Standard) ☐ 90℃ ☐ 120℃ ☐ その他( )
・Fluid		☐ Non-Corrosive ☐ Corrosive *If corrosive, please specify ( )
・Seal Material Request	Body	☐ None（Standard: FKM) ☐ Yes *Please specify ( )
	Gate	☐ None（Standard: FKM) ☐ Yes *Please specify ( )
・Material Request	Body	☐ Molded AL（Standard) ☐ Other ( )
	Gate	☐ AL（Standard) ☐ Other( )
・Surface Treatment		☐ Not requi ☐ Required *Please specify if required( )
・Heat Application Requirement	Body	☐ None ☐ Yes *Please specify temperature if required(℃)
	Gate	☐ None ☐ Yes *Please specify temperature if required(℃)
・Open-Close Time Req't		☐ No ☐ Yes *Please specify time if required (s)
・Installation Orientation		☐ Port is horizontal ☐ Port is Vertical
・Open-Close Sensor		☐ Non-contact Reed Switch（Stan ☐ Other *Please specify if requested ( )
・Note（Supplement, Special Request etc.)		